

Description

The Exterior Siren/Strobe Model SE650 is a battery operated, wireless combination unit designed for use in RSAlarm™ security systems.

The unit consists of a speaker, stroblight, and S2View® spread spectrum, videofied, interactive, encrypted wireless circuitry for secure two-way communication with the control panel.

The siren produces an output level of 105 dB at 1 meter for three minutes, in alarm. The strobe light flashes four times per second for three minutes, in alarm.

The unit is typically installed outdoors on the premises structure to help responding authorities locate the alarm site. The unit should be mounted where it is protected from weather elements, at a height where intruders cannot reach to help prevent disabling the unit. A dual tamper function provides detection for both unit removal from the base or mounting surface.

The unit is powered by four alkaline batteries that can last seven years or more, depending on the amount of siren/strobe activity. The unit transmits a check-in signal every eight minutes that includes its unique identification code, along with the tamper condition and battery status.

Features

- ▶ *S2View® – Spread Spectrum, Videofied, Interactive AES Encrypted Wireless technology provides optimum signal integrity and security.*
- ▶ *Speaker – provides output of 105 dB @1 meter for up to three minutes, in alarm.*
- ▶ *Supervised – transmits a check-in/status signal every 8 minutes indicating tamper state and battery status.*
- ▶ *Dual tamper – provides detection for both wall and cover tamper.*
- ▶ *Alkaline batteries – last at least seven years (estimated).*

Applications

- ▶ *Visual and audible annunciation of alarms in RSAlarm security systems.*



Electrical Data

Power requirements	Four 1.5 V batteries
Battery type	Alkaline, D size
Battery life (estimated)	At least 7 years
RF technology	S2View®
Radio type	Spread Spectrum Bidirectional
Operating frequency	915 MHz. 25 frequencies
Transmission security	AES encryption algorithm
Supervision	Transmits check-in signal every 8 minutes
Antenna	Integrated
Tamper detection	Wall and cover tampered
Speaker impedance	4 ohms
Output level	105 dB @ 1 meter
Output duration	Three minutes maximum
Flash type	Strobe light tube
Flash duration	Three minutes maximum
Flash sequence	Four flashes/sec
Operating temperature	-13° - 158° F (-25° - 70° C)
Maximum relative humidity	70%, non-condensing
UL Listings	1023 (applied for)

Physical Data

Material	ABS-ULVO
Dimensions	(LxWxD): 9 in. x 6-1/2 in. x 3 in. (227 mm x 166 mm x 80 mm)
Weight	31 oz./880 g (without batteries)

Installation/Mounting

Unit/Base	Two screws secure unit to base; three screws secure unit base to mounting surface.v
-----------	---



4455 White Bear Parkway, Suite 700
White Bear Lake, MN 55110
USA

Toll Free: 877-206-5800
Fax: 763-784-0200
www.videofied.com